

**Policy No 12/2018**

Tele : 23019646

E2 Works (PPC) Sub Dte  
Dte of Works, E-in-C's Branch  
Integrated HQ of MoD (Army)  
Kashmir House, Rajaji Marg,  
New Delhi – 110011.

A/37696/12-147/Pol/E2W (PPC)

04 Oct 18

**List 'A' & 'B'**

**GUIDELINES FOR FLEXIBLE PAVEMENT IN  
CANTONMENTS MILITARY STATIONS**

1. Reference this HQ letter of even No dated 30 Oct 14 (Policy No 22/2014).
2. Design of all new roads shall be carried out based on likely traffic data (in million standard axle) and soil parameters (CBR), as per IRC : 37-2012 and Ministry of Road Transport and Highways, Specifications for Road and Bridge Works (Fifth Revision).
3. Resurfacing, strengthening and maintenance of roads shall be based on IRC : 81-1997 and IRC : 37-2012. Minimum thickness of wearing course (Bituminous Concrete) for resurfacing/ maintenance be adopted as under: -
  - (a) Heavy rainfall, coastal and heavy traffic density areas - 40 mm
  - (b) Other areas - 30 mm
4. The mechanical/ sensor paver will be used for all pavement works.
5. This supersedes Policy No 22/2014 dated 30 Oct 14 mentioned at Para 1 above.



(Mohit Nautiyal)  
Brig  
DDGW (PPC & Est)  
For E-in-C

Copy to:-

**QMG's Branch / DG LWE**

**IHQ of MoD (Navy) / Dte of Works**

**IHQ of MoD (AF) / Dte of Works**

**Coast Guard HQ (Works Dte)**

**HQ IDS / Dte of Works**

**QMG's Branch / ADG TE**

Internal

**All Sub Dtes of Wks Dte**

**Automation Cell**

- For uploading on MES Website.